RUST BUSTER

VIDEO AVAILABLE

REQUIRED TOOLS	KIT CONTAINS	QTY
Jack Stands or Lift	Rear Cab Mount	1
Paint/Primer	M10 Flanged Hex Screw	6
Hand Grinder	M10 Flange Locknut	6
Cutting Wheel or Torch		
Ear & Eye Protection		
Sockets & Ratchet		
Fire Extinguisher		
Wrench		

RB7358

1) **PREPARING YOUR VEHICLE**
Begin by disconnecting your battery prior to starting your installation.

Inspect your vehicle for leaking fuel lines, fuel tank and engine components. If you have fuel leaks repair all leaks prior to starting your installation. If your fuel tank is near your welding area **remove your tank prior to welding.**

Remove all combustible items above the work area such as seats, carpets, padding, etc.

Keep all flammable materials away from the vehicle work area.

2) **PREPARING YOUR WORKSTATION**
Keep a fire extinguisher close by in the case of fire and make sure you always have a designated "Fire Watch" to assist during the cutting or welding phases.

Abide by all apprenticed welding safety standards and practices.

Always use appropriate welding eye protection, ear protection, and work and fire safety gloves during the installation and within the work area.

WARNING!

If you are unsure on how to perform the installation or how to operate any of the required tools listed above, it is **HIGHLY** advised that you enlist the work of a certified welder/installer.

Failure to follow proper safety precautions and instructions may result in serious injury. **The user assumes all liability when installing the product.**

3) **PREPARING FOR YOUR INSTALL**
Lift up your vehicle.

4) **CUT**
Remove the rivets retaining the factory rear cab mount,

5) **INSTALL**
Using a 14mm socket and 15mm wrench, install the bolts holding on your rear cab mount.

6) **PAINT**
Paint the part with primer or other rust inhibitor to help prevent or reduce the risk of rust formation.

We recommend our Rust Buster Rust Converter & Primer Spray Paint (RB9917).

RB7358